

RESIDENTIAL REVERSE OSMOSIS SELECTION GUIDE

DRO-100 DRO-100-HE PLUS NATURES BALANCED STRUCTURED WATER









| GALLONS DAILY TREATED WATER | 100 | 100 | 100 | 100 |
|---|-------------|-------------|-------------|-------------|
| PRODUCT : DRAIN RATIO | 1: 1 | 1.4 : 1 | 1:1 | 1.4:1 |
| UNIT SIZE W X H X D – INCH | 16 x 19 x 6 |
| TANK SIZE DIA. X HEIGHT – INCH | 11 x 14.5 | 11 x 14.5 | 11 x 14.5 | 11 x 14.5 |
| TANK GALLONS IN STORAGE ⁽¹⁾ | 2.6 | 2.6 | 2.6 | 2.6 |
| WATER QUALITY METER | NO | NO | YES | NO |
| NUMBER OF TREATMENT STEPS ⁽²⁾ | 4 | 9 | 10 | 11 |
| REMINERALIZER | NO | YES | YES | NO |
| TYPICAL TDS REDUCTION ⁽³⁾⁻ - % | 90 | 95 | 90 | 95 |
| HEMOTITE AND CRYSTALS | NO | YES | YES | YES |
| NEODYMIUM MAGNETIC FIELD | NO | YES | NO | YES |
| STRUCTURED WATER CELL | NO | NO | NO | YES |
| VORTEX | NO | NO | NO | YES |

NOTES: (1) BASED ON 60 PSI FEED, 8 PSI PRE-CHARGE, AUTO SHUT-OFF AT 48 PSI. (2) CUSTOM FILTERS USED THAT PERFORM MORE THAN ONE FUNCTION. (3) BASED ON 60 PSI FEED, TDS <400 PPM, 77° F

AND TEST BEFORE POST TREATMENT. HIGHER VALUES TO NON-ELECTRIC PERMEATE PUMP TO ELIMINATE TDS CREEP.